

# StormPit®

SURFACE WATER SUMPS

**Built for Compliance.**

# StormPit Type One



**THE APD STORMPIT RANGE HAS IT  
ALL PLUS MORE!**

Don't be fooled by non-compliant sumps and ensure you are complying to 'NZ Building Code E1 Surface Water' by installing the APD StormPit Type One sump today.

**EASIER!  
FASTER!  
IMPROVED!**


## **NZBC E1 TYPE ONE COMPLIANT SUMPS ARE REQUIRED TO HAVE**

- 300mm opening.
- Maximum 1000mm height.
- 375mm diameter.
- Removable access cap for cleaning.
- A submerged or trapped outlet.
- 300mm minimum at base for silt settlement.
- Minimum 90mm outlet pipe.

APD's StormPit range offers more than just compliance to NZBC E1, we have designed additional features to benefit the installer onsite and ensure the long-term, trouble-free use.

## **ADDITIONAL FEATURES**

- 5 tonne rated ductile iron grate fits into the main body for shallow depth installations.
- Adjustable in height from 171mm – 445mm from top of outlet pipe to finished ground level.
- 274mm of height adjustment.
- 3 x Moulded inlet connections sized for 100mm PVC.
- Full 100mm sized outlet with oversized trap for greater flow.
- Anti-flotation ring.
- No threads that can bind up with gravels and fines.
- Easy to remove access cap.



For more information contact  
your APD account manager  
or call (09) 263 7741

**www.apd.co.nz**



IDEAL TANK & SYSTEM SOLUTIONS

May 2021